

## Mallas soldadas SIMA Línea Estándar

MODELO	SEPARACION		DIAM. ALAMBRES		PESO	
	Long. cm	Transv. cm	Long. mm	Transv. mm	Panel Kg	Por m2 Kg/m2

### Cuadrícula cuadrada

Q 50	25	25	4.0	4.0	10.45	0.81
Q 84	15	15	4.0	4.0	17.42	1.35
Q 92	15	15	4.2	4.2	15.18	1.49
Q 126	10	10	4.0	4.0	25.84	2.00
Q 188	15	15	6.0	6.0	39.07	3.03
Q 335	15	15	8.0	8.0	69.52	5.39
Q 524	15	15	10.0	10.0	108.59	8.42

### Cuadrícula rectangular

R 84	15	25	4.0	4.0	14.02	1.09
R 92	15	25	4.2	4.2	15.43	1.20

Paneles de 2.15 x 6 m (sup. 12.9 m2) Norma IRAMIIAS U 500-06 tipo AM-500

## Mallas Job Shop Galvanizados / Negras

MODELO	SEPARACION		DIAM. ALAMBRES		PESO	
	Long.	Transv.	Long.	Transv.	Panel	m2

### En paneles con salientes

Q 109	50	25	2.6	2.6	6.19	1.72
Q 141	50	15	3.0	3.0	7.99	2.22
Q 182	50	15	3.4	3.4	10.13	2.81
Q 216	25	10	2.6	2.6	12.38	3.44
R 85	50	15	3.0	3.0	10.66	2.96
R 216	25	15	2.6	2.6	10.22	2.84
R 282	25	15	3.0	3.0	13.19	3.66

### En paneles sin salientes

Q 109 SS	50	50	2.6	2.6	6.32	1.76
Q 141 SS	50	50	3	3	8.16	2.27